Use only the external power supply that comes with your hub. Beginning in the fall of 2015, a 12V 2A power supply will be included with the U360-007, whereas previous units included a 5V 4A power supply. The power spec printed under the DC jack on your hub will match the spec of the included power supply.

7-Port USB 3.0 SuperSpeed Hub with USB Charging

MODEL NUMBER: **U360-007**

Connects to the USB 3.0 port on your laptop, Ultrabook or computer to give you seven external USB 3.0 ports.

Description

Tripp Lite's U360-007 USB 3.0 Hub plugs into a computer's USB 3.0 port and provides seven USB 3.0 SuperSpeed peripheral ports, as well as USB charging. Plug-and-Play... no software or drivers required. Automatically switches to the highest speed supported by the peripheral. Windows (compatible with Windows 10) and Mac compatible.

Features

- 7-Port USB 3.0 SuperSpeed Hub with USB Charging
- Supports USB 3.0 5Gbps transfer speeds when plugged into a USB 3.0 computer and peripheral
- Each USB-A port is capable of delivering up to 5V, 2.4A and is USB Battery Charging (BC) specification v1.2 compliant
- The included external power supply provides 12V 2A of power, to be shared between the hubs ports
- Plug-and-Play
- No software or drivers required
- Windows (compatible with Windows 10) and Mac compatible
- Overcurrent protection
- LED power indicator light

Highlights

- USB 3.0 Hub with 7 USB 3.0 SuperSpeed ports and USB Charging
- Plug-and-Play - no software or drivers required
- All 7 USB-A ports provide up to 5V, 2.4A of charging power each and are USB Battery Charging (BC) specification v1.2 compliant.

System Requirements

- Computer with an available USB 3.0 port
- USB peripherals (backward compatible with previous USB generations)
- Use only the external power supply that comes with your hub. Beginning in the fall of 2015, a 12V 2A power supply will be included with the U360-007, whereas previous units included a 5V 4A power supply. The power spec printed under the DC jack on your hub will match the spec of the included power supply.

Package Includes

- USB 3.0 7-port Hub with USB Charging
- USB 3.0 A-B cable, 3ft
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.8A Max / Output: 12V, 2A)

Specifications

OVERVIEW	
UPC Code	037332178480
AC Adapter	Input: 100-240V, 50/60Hz, 0.8A Max / Output: 12V, 2A
Over Current Protection	2.93A
Technology	USB (all versions); USB 3.0 (SuperSpeed)

OUTPUT	
Charging Ports / Amps	(1) 2A

INPUT	
Voltage Compatibility (VAC)	100; 110; 120; 127; 200; 208; 220; 230; 240
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 1.5A
External Power Supply Output Specs (V / A)	12V / 3A
External Power Supply Cord Length (ft.)	5
External Power Supply DC Barrel Connector Specs	OD: 5.5 x 2.5 x 10mm, Positive Pin, Negative Sleeve
External Power Supply Plug(s)	NEMA 1-15P North America
External Power Supply Certifications	cUL; RoHS
Bus Powered	No

USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Blue (Power)

PHYSICAL	
Shipping Dimensions (hwd / in.)	5.510 x 5.910 x 3.540
Shipping Dimensions (hwd / cm)	14.00 x 15.01 x 8.99
Shipping Weight (lbs.)	0.7900
Shipping Weight (kg)	0.36
Unit Packaging Type	Box
Unit Dimensions (hwd / in.)	0.87 x 6.1 x 2
Unit Weight (lbs.)	0.00
Unit Weight (kg)	0.00
Material of Construction	ABS
Color	Black

ENVIRONMENTAL	
Operating Temperature Range	-4 to 158 F (-20 to 70 C)
Storage Temperature Range	-4 to 185 F (-20 to 85 C)
Relative Humidity	20% to 80% RH, Non-Condensing
BTUs	4.8 BTU/Hr
Power Consumption (Watts)	1.4
Power Provided to Connected Device(s)	5V 0.9A (4.5W) Output (USB-A 3.0), 5V 2A (10W) Output (USB 2A Charger)
CONNECTIONS	
Ports	7
Side A - Connector 1	USB 3.0 A (MALE)
Side B - Connector 1	(7) USB 3.0 A (FEMALE)
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
CERTIFICATIONS	
Certifications	Tested to CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty